



N\*(2 POLE 3600 RPM) / L\*(4 POLE 1800 RPM)

N5/L5	34 1/4 [870]	30 1/4 [768]	29 3/4 [756]	27 3/4 [705]
N4/L4	30 1/4 [768]	26 1/4 [667]	25 3/4 [654]	23 3/4 [603]
N3/L3	28 3/4 [730]	24 3/4 [629]	24 1/4 [616]	22 1/4 [565]
N2/L2	26 1/2 [673]	22 1/2 [572]	22 [559]	20 [508]
N1/L1	25 1/2 [648]	21 1/2 [546]	21 [533]	19 [483]
MOTOR	A	B	C	D

**TEIKOKU USA INC**  
CHEMPUMP  
Containment, Reliability & Safety by Design

UNLESS OTHERWISE STATED,  
-ALL UNITS IN INCHES  
-DIMS. IN BRACKETS ARE IN mm  
-DIMS. MARKED \* ARE ±1/16 [±2]  
-ALL OTHER DIMS. ARE ±1/4 [±6]  
-ANGLE DIMS. ARE ±5  
NOTE: ROUNDING TO NEAREST INCH/mm PRECLUDES INCH/mm CONVERSION.

DRAWN: MJD, DATE: 6/13/18  
CHECKED: JHW, DATE: 7/12/18  
APPROVED: CMH, DATE: 7/12/18

TITLE: OUTLINE  
NC-A50-8 & 10  
150# (TRG MONITOR)

SCALE: 1:4

DRAWING NO. C  
REV. 60579 0

NO.	DATE & PRO. NO.	REVISIONS	BY