



N\*(2 POLE 3600 RPM) / L\*(4 POLE 1800 RPM)

N5/L5	34 1/4 [870]	30 1/4 [768]	29 3/4 [756]	27 3/4 [705]
N4/L4	30 1/4 [768]	26 1/4 [667]	25 3/4 [654]	23 3/4 [603]
N3/L3	28 3/4 [730]	24 3/4 [629]	24 1/4 [616]	22 1/4 [565]
N2/L2	26 1/2 [673]	22 1/2 [572]	22 [559]	20 [508]
N1/L1	25 1/2 [648]	21 1/2 [546]	21 [533]	19 [483]
MOTOR	[A]	[B]	[C]	[D]

NO.	DATE & PRO. NO.	REVISIONS	BY

**TEIKOKU USA INC**  
**CHEMPUMP**  
Containment, Reliability & Safety by Design

UNLESS OTHERWISE STATED, -ALL UNITS IN INCHES -DIMS. IN BRACKETS ARE IN mm -DIMS. MARKED * ARE ±1/16 [±2] -ALL OTHER DIMS. ARE ±1/4 [±6] -ANGLE DIMS. ARE ±5 NOTE: ROUNDING TO NEAREST INCH/mm PRECLUDES INCH/mm CONVERSION.	DRAWN MJD 6/13/18	DATE 6/13/18	TITLE OUTLINE NC-A50-8 & 10 300# (TRG MONITOR)
CHECKED JHW 7/12/18	APPROVED CMH 7/12/18	SCALE 1:4	DRAWING NO. C 60580
			REV. 0